

Accessories for PTC thermistor type level sensors



GWG filler cap

For fuel oil EL „standard“, diesel and bio-diesel. Bayonet connection G2 according to EN 14420-6 with integrated level sensor connection fitting. Male coupling made of brass. Filler cap made of oil- and weather resistant plastic. Lockable.



GWG filler cap – green

For low sulphur fuel oil EL (green colour code). With red plate also approved for fuel oil EL „standard“, diesel and bio-diesel. Bayonet connection G2 according to EN 14420-6 with integrated level sensor connection fitting. Male coupling made of brass. Filler cap made of oil- and weather resistant plastic. Lockable. Red plate (Also for fuel oil EL „standard“) is included. Please refer to page 109 for additional filler caps.



Cable extension fitting KVA

Cable extension fitting for 2-core electrical cables (max. 42 V/4 A). Clamp glands on both sides for cable diameters between 6 and 8.3 mm.

Reducer G1½ x G1

Reducer G1½ x G1 made of grey plastic (ABS).

Reducer G2 x G1½

Reducer G2 x G1½ made of grey plastic (ABS).

New directives:

- The filler cap without colour code must only be used with systems which are exclusively used with fuel oil EL „standard“, diesel and bio-diesel.
- The **green** filler cap must only be used with systems which are exclusively used with low sulphur fuel oil EL.
- The **green** filler cap in conjunction with the **red plate** (Also for fuel oil EL „standard“) must only be used with systems using low sulphur fuel oil EL, EL „standard“, diesel and bio-diesel.



Please refer to page 470 for a complete range of GWG level sensor test instruments.



Please refer to page 59 for GWG fittings.

Check www.schwefelarmesheizoel.de to see whether the various units of a heating systems are suitable for use with low sulphur fuel oil EL.

DG: G	PU	Part no.	Preis €
GWG filler cap	10	20430	
GWG filler cap – green	10	20443	
Reducer G1½ x G1	10	20905	
Reducer G2 x G1½	10	20903	
Cable extension fitting KVA	10	40041	