

Tank fittings, overpressure devices



GWG filler cap

For fuel oil EL standard, diesel and bio-diesel. Bayonet connection G2 according to DIN EN 14420-6 with integrated level sensor connection fitting. Male coupling made from brass. Filler cap made from oil- and weather resistant plastic. Lockable.

Filler cap

Similar to GWG filler cap, but without the level sensor plug.



GWG filler cap – green

For low sulphur fuel oil EL (green colour code). Bayonet connection G2 according to DIN EN 14420-6 with integrated level sensor connection fitting. Brass male coupling. Filler cap made from oil- and weather-resistant plastic. Lockable. Red plate („Also for fuel oil EL standard“) is included. (Refer to page 57)



Overpressure device

Prevents overpressurisation of storage tanks during filling. G1 $\frac{1}{2}$ male threaded connection. Opens to release pressure at approx. 25 mbar. Two or more overpressure devices must be installed for filling rates of more than 300 l/min.

DG: G	PU	Part no.	Price €
GWG filler cap	10	20430	
GWG filler cap – green	10	20443	
Filler cap K	10	20440	
Overpressure device	25	20466	



DG: G	PU	Part no.	Price €
Dip tube cap G1 x 1$\frac{1}{4}$	25	20464	
Filler cap G2 x 2$\frac{1}{2}$ Heavy duty version, fuel oil EL standard	55	20445	
Filler cap – green G2 x 2$\frac{1}{2}$ Heavy duty version, fuel oil EL low sulphur	25	20452	
Vent caps			
Vent cap 2" plastic – push-on	25	20460	
Vent cap 1$\frac{1}{2}$" plastic – push-on	25	20450	
Vent cap G2 plastic – male thread	25	20462	
Vent cap G2 metal	25	20463	
Vent cap G1$\frac{1}{2}$ metal	25	20455	