

Questionnaire/Checklist for enquiries Thermometers

Company:	Project/enquiry:
Quantity	
Application	
Medium to be measured	
Version	☐ Bimetal thermometer ☐ Gas filled thermometer
Housing diameter	□ 34 □ 50 □ 63 □ 80 □ 100 □ 160 □ 250
Range	
Connection	☐ Bottom ☐ Back ☐ Rotatable or pivoted
Connection type	☐ Plain stem ☐ Loose male connection ☐ Sep. screw-in thermowell ☐ Loose union nut ☐ Sep. weld-in thermowell ☐ Compression fitting, adjustable ☐ DIN/EN thermowell ☐ Fixed male connection Neck ☐ No ☐ Yesmm
Connection thread	☐ G ☐ NPT ☐ BSPT ☐ For welding ☐ 1/4 ☐ 3/8 ☐ 1/2 ☐ 3/4 ☐ Other:
Stem length	
Mounting for capillary type	☐ Bracket for wall mounting ☐ Back flange ☐ 3-hole fixing panel mounting bezel
Capillary length	
Housing	☐ Plastic ☐ Sheet steel ☐ Stainless steel with push on bezel ☐ Stainless steel with bayonet type bezel
Filling	☐ Without ☐ Glycerine ☐ Silicone oil ☐ Other:
Stem material	☐ Brass ☐ Stainless steel 1.4571/1.4541 ☐ Other:
Thermowell material	☐ Brass ☐ Steel ☐ Stainless steel ☐ Other:
Dial	☐ Single scale as per EN ☐ Dual scale: ☐ Special scale: Customer's logo ☐ Yes ☐ No Manufacturer's logo ☐ Yes ☐ No
Accuracy	Class 1 2 According to EN 13190
Electrical contacts (only for gas filled thermometers)	 No Magnetic spring contact ☐ Inductive contact ☐ Electronic contact Single ☐ Double ☐ Triple Switching function:
Other	